

# Index

$\beta$ , 99  
 $\Delta E_{TL}$ , 133  
4-AFC metric, 94

## A

acceptance angle, 16  
accommodation, 107  
achromatic, 29  
acoustical noise, 209  
ACR Standard for Teleradiology, 143  
active-matrix liquid crystal display,  
  *see* AMLCD  
adaptation, 105  
additive color, 17, 40  
addressability  
  and screen size, 54  
  as part of measurement definition, 162  
  consideration in equipment selection, 201  
  control, 44  
  defined, 33  
  minimum, 166  
  procedure for measuring, 171  
addressable pixels, 30  
aerial imagery, 143  
age  
  of monitor, 74  
  of observer, 121  
aim curves, 256  
aim functions, 256  
aliasing, 75  
alternating current, 43  
alternatives to measurement, 194  
ambient light, 16, 204–205, 208  
AMLCD, 29, 41  
amplified beam current, 34  
amplified voltage, 34  
amplitude, 31  
analog  
  device, 29  
  signal, 31  
  TV, 31  
angular disparity, 110  
annotation capability, 199  
ANSI lumens, 258  
antireflection coating, 38  
application-specific integrated circuits,  
  201  
array scanners, 237  
artifacts, 53, 74, 184, 186, 192

astigmatism, 121  
average signal level, 71

## B

banding, 252  
bandwidth, 229  
bandwidth compression, 219, 229  
barrel, 203  
Barten contrast sensitivity model, 126  
Bartleson, 255  
beta ( $\beta$ ), 99  
bicubic interpolation, 228  
bilinear interpolation, 163, 228  
binary decision, 84  
binocular vision, 110  
bit depth, 33, 145, 153, 241  
blackbody, 49  
Blackwell, R., 124  
blemishes, 75  
blurring, 253  
bone cortex, 231  
Briggs  
  color ratings, 140  
  scores, 91, 95, 212  
  target, 88–89, 93  
brightness, 15, 17, 44  
brightness nonuniformities, 184

## C

calibration  
  of printer, 254  
  source, 17  
camera exposure meter, 16  
candelas, 13  
capture device, 1, 6  
cathode, 36  
cathode-ray tube, *see* CRT  
CCD  
  array, 17  
  response to light energy, 238  
CD accompanying book, contents of, 8  
center area of monitor, 62  
charge-coupled device, *see* CCD  
checkerboards, 89  
checkers, 90  
chest images, 142, 231  
chroma, 23  
CIE (Commission Internationale de l'Éclairage), 17

- CIE  $L^*a^*b^*$ , 133  
 CL, *see* command level  
 CL/luminance function, 211  
 clock frequency, 201  
 clutter, 130  
 Cm, *see* contrast modulation  
 CMYK, 25  
 cognitive measures, 8  
 cognitive system, 81  
 coherent illumination, 130  
 color  
   bit depth, 44  
   blindness, 123  
   Briggs, 140  
   Briggs target, 93  
   casts, 38, 147  
   constancy, 110  
   controls, 44  
   CRT, 40  
   differences, 117  
   fringing, 253  
   gain, 44, 49  
   laser printers, 249  
   matching, 252  
   measurement, 11, 17  
   misregistration, 253  
   monitors, 44, 54, 70, 137  
   purity, 40  
   temperature, 44, 48, 139, 154, 147  
   tracking, 70  
   transforms, 223  
   uniformity, 155  
   vision deficiencies, 123  
   vs. monochrome monitor selection, 200  
 colorfulness, 23  
 colorimeter, 26  
 colors displayed, number of, 49  
 command level (CL)  
   defined, 22  
   and luminance, 211–212  
 computed radiography, 231  
 computed tomography (CT), 1, 145  
 computer memory (CPU), 34  
 cones, 107  
 confidence ratings, 84  
 contouring, 145  
 contrast, 44, 53  
 contrast modulation (Cm), 61, 162, 166  
   Zone A, 172  
   Zone B, 172  
 contrast ratio, 66  
 contrast sensitivity, 112  
 controller, 201  
 convergence, 56  
 convolution kernel, 224  
 coordinate system, 17  
 cornea, 107  
 corrective lenses, 121  
 correlation between CL and luminance, 212  
 correlation coefficient, 163  
 criteria scaling, 85  
 Crites, 212  
 CRT  
   as display type, 29  
   color, 39–40  
   flat panel, 39  
   operation  
     efficiency of, 38  
     role of electrons in, 34  
 CT, *see* computed tomography  
 cycle, 57
- D**
- $d'$ , 99  
 decibels (dB), 138  
 degaussing control, 209  
 delta pulse code modulation, 230  
 density uniformity, 252  
 desired values, 138  
 detective quantum efficiency (DQE), 74  
 diagonal, 54  
 diagonal pitch, 173  
 dichromats, 123  
 differential receiver operating characteristic (DROC),  
   101  
 diffuse reflection, 68  
 digital brightness and contrast, 201  
 digital frequency, 31  
 digital signal, 31  
 digital-to-analog converter, 138  
 digitizer, 237  
   device selection, 239  
   image quality, 239  
   operation, 237  
   resolution, 240  
 digitizing, 237  
   procedures, 243  
   resolution, 244–245  
 direct optical projection, 248  
 discrete cosine transform, 230  
 dispenser cathode, 36  
 display  
   controller, 5, 31  
   frequency control, 44  
   quality metrics, 8  
   system, 5  
 distortions, 53, 74  
 Doppler ultrasound, 223  
 dot density, 244  
 double stimulus continuous quality scale,  
   83  
 double stimulus impairment scale, 83  
 DQE, *see* detective quantum efficiency

- DR  
 adjustment (DRA), 219–220  
 defined, 66  
 to measure luminance, 138, 149  
 to measure radiometric fidelity, 240, 251  
 DRA, *see* DR adjustment  
 drift, 74, 181, 183, 189  
 DROC, *see* differential receiver operating characteristic  
 drum microdensitometers, 237  
 dye  
 diffusion, 249  
 sublimation, 249  
 dynamic black-level stability, 69  
 dynamic focusing, 36  
 dynamic range, *see* DR
- E**
- edge  
 response, 60  
 sharpness, 59  
 efficiency of CRT operation, 38  
 egg crate diffusers, 207  
 electron gun, 36  
 electronic projection devices, 2  
 electrons, role in CRT operation, 34  
 electrostatic lens system, 36  
 electrostatic printers, 249  
 emitted energy, 11  
 emulsion, 243  
 environmental controls, 199  
 ergonomic considerations, 209  
 etching, 38  
 event distributions, 99  
 exposure  
 meter, 155  
 value, 155  
 extinction  
 level, 184  
 ratio, 182, 192
- F**
- face plate, 38  
 far-sightedness, 121  
 fast Fourier transform, 73  
 fast intelligent tracking, 40  
 FEDs, *see* field-emissive displays  
 field of view, 16  
 field-emissive displays (FEDs), 29  
 film  
 annotation and loading, 243  
 digitizers, 1  
 resolution, 240  
 fixation, 102, 109  
 flatbed microdensitometers, 237  
 flatbed linear scanners, 238  
 flat-panel displays, 29  
 flicker, 74, 183  
 flicker mechanism, 110  
 footcandle, 13  
 foot-lamberts defined, 13  
 fovea, 107  
 foveal vision, 109  
 frame grabbers, 237  
 free-response operating characteristic (FROC), 101  
 frequency, 31  
 frequency filtering, 227  
 FROC, *see* free-response operating characteristic
- G**
- gamma, 34, 66, 147  
 gamut, 22, 70, 148, 251  
 geometric correction, 242  
 geometric distortion, 75  
 controls, 44  
 geometric fidelity, 239, 242, 249  
 geometric transforms, 219, 227  
 ghosting, 75, 184  
 graphics acceleration, 34  
 graphics cards, 31  
 gray-level reversal, 71  
 gray-scale images, 223  
 grid, 36
- H**
- halation, 67, 139, 145, 153  
 half-power level, 56  
 halftone printing, 244, 250  
 hard-copy imagery, 1  
 haze component, 68  
 HDTV, *see* high-definition TV  
 high-definition TV (HDTV), 30  
 high-frequency boost, 224  
 horizontal pitch, 173  
 HSB space, *see* hue/saturation/brightness space  
 hue  
 defined, 17  
 differences, 24  
 with color imagery, 223  
 hue/saturation/brightness (HSB) space, 24  
 human observer, 3  
 human visual system (HVS), 6, 8, 105  
 individual differences in, 119  
 hyperspectral, 231
- I**
- IDEX  
 function, 214  
 system, 125

- illuminance, 13  
 illuminance photometer, 15  
 image  
   chain, 1  
   compression, 230  
   interpretability, 85  
   motion, 115  
   room, 182  
   scaling, 85  
 Image Display and Exploitation system,  
   *see* IDEX  
 Imagery Interpretability Rating Scale, 81  
 impedance, 201, 203  
 individual differences in HVS, 119  
 information technology (IT) personnel, 7  
 information theory, 187  
 initial setup, 149  
 initialization and prescan, 243  
 inkjet printers, 249  
 input/output function, *see* I/O function  
 instantaneous signal level, 71  
 Integrated Exploitation Capability, 137  
 interface requirements, 201  
 interlaced scan, 36  
 internal noise, 126  
 interpolated resolution, 240  
 I/O function, 42, 67, 147, 150  
 ionized gas, 43  
 iris, 105
- J**
- “J” curve, 111  
 jitter, 74, 181–183, 189–190  
 JPEG, 230  
 JPEG 2000, 230
- K**
- kernel, 226
- L**
- $L^*a^*b^*$  space, 22  
 $L^*u^*v^*$ , 20, 133  
 LaGrange interpolator, 228  
 landscape monitor mode, 30  
 large-scale uniformity, 240–241, 251  
 laser digitizers, 238  
 lateral disparity, 111, 117  
 lateral inhibition, 126  
 lens of human eye, 107  
 lens flare, 148  
 lesion margins, 231  
 light  
   box, 141, 256  
   energy, 37  
   level, 2  
   measurement of, 11  
   output, 258  
   sensitivity, 109  
 lightness, 223  
 linear TTA, 221  
 linearity, 46, 183, 188, 194, 240  
 liquid crystals, 41  
 Lmax, 139, 150  
 Lmin, 139  
 logarithmic amplifier, 238  
 look-up tables, 67  
 low-pass filter, 226  
 lumen, 11  
 luminance, 53, 77  
   controls, 44  
   JNDs, 139, 146  
   loading, 69  
   nonuniformity, 69, 144  
   parameters, 137  
   requirements  
     color, 138  
     monochrome, 139  
     stereo, 139  
   stability, 69, 147  
   step response, 182, 190  
   uniformity, 69, 150  
 luminescent phosphor, 34  
 luminous efficiency function, 21  
 luminous power, 11  
 lux, 13
- M**
- MacAdam ellipses, 20  
 macro jitter, 182, 190  
 magnetic  
   environments, 200  
   fields, 148, 200, 208  
   resonance imaging, *see* MRI  
 magnification, 227  
 magnitude, 31  
 mammograms, 143, 212  
 mammographic reading rooms, 206  
 marker images, 85  
 matching, 252  
 matrix (CCD array) photometer, 173  
 matrix displays, 43, 73  
 maximum luminance, 139  
 measurement  
   alternatives, 194  
   domains, 53  
   pucks, 16  
 mesopic vision, 115  
 micro jitter, 182, 190  
 microdensitometer, 237–238  
 microphotometer, 17

milli-lambert, 15  
 minification, 227  
 minimum addressability, 166  
 minimum performance levels, 138  
 modulation threshold, 113, 213  
 modulation transfer function, *see* MTF  
 moiré, 75, 182–183, 191  
 monitor  
   aging of, 74, 144  
   and video controller selection, 199  
   calibration, 209  
   center area of, 62  
   color, 44, 54, 70, 137  
   connection, 203  
   environment, 204  
   landscape mode, 30  
   monochrome, 29, 137  
   peripheral area of, 62  
   portrait mode, 30  
   setup, 203  
   size/resolution requirements, 161–162  
   surround, 208  
   type selection, 199–200  
 monochromatic vision, 123  
 monochrome monitors, 29, 137  
 monochrome (luminance) models, 124  
 monocular vision, 110  
 motion imagery, 232  
 MPEG-1, 232  
 MPEG-2, 232  
 MPEG-4, 232  
 MRI, 145  
   scan, 3  
 MTF, 63  
   compensation, 224  
   of the eye, 113  
 MTFC, 224  
 multiple-purpose monitor, 199  
 multispectral  
   imagery, 212  
   NIIRS, 140  
   scanners, 1  
 multisync, 199  
 Munsell system, 17  
 mura, 75, 182, 184, 192  
 myopes, 120  
  
**N**  
 National Imagery and Mapping Agency,  
   *see* NIMA  
 National Imagery Interpretability Rating Scale, *see*  
   NIIRS  
 National Information Display Laboratory, *see* NIDL  
 nearest-neighbor resampling, 228  
 near-lossless archival storage, 243  
 near-sightedness, 119

NEMA/DICOM, 212  
   calibration, 206  
   perceptual linearization function, 128  
 neon glow lamps, 43  
 nerve cells, 109  
 neural impulses, 109  
 neural network processing, 1  
 NIDL, 17, 137  
 NIIRS, 2, 85  
   ratings, 95  
   variability, 87  
 NIMA, 137  
 NIST, 17  
 nit, 15  
 noise  
   adjustment control, 47  
   generally, 53, 71, 240–241, 251, 253  
   types of  
     acoustical, 209  
     frequency-dependent, 186  
     pink, 186  
     spatial, 186  
     temporal, 186  
     time-independent, 186  
     white, 186  
   noise-equivalent quanta, 74  
   noise power, 73  
   noise power spectrum, 74  
   noncoherent illumination, 130  
   noncommandable pixels, 42  
   nonlinear TTA, 221  
   nonuniform energy distribution, 56  
   nonuniformities, 184

## O

objective perceptual quality measures, 87  
 objective performance measures, 96  
 objective quality measures, 82  
 optical resolution, 240  
 organic light-emitting diodes, 29  
 overshoot, 69  
 oxide cathode, 36  
 oxide coating, 36

## P

paper print, 256  
 PDP, 29, 43  
 perceptible acuity, 111  
 perception of depth, 110  
 perceptual linearization, 4, 67, 201, 210  
 perceptual measures, 8, 81  
 performance measurement alternatives, 194  
 peripheral area of monitor, 62  
 peripheral vision, 109  
 periphery of retina, 107

- phosphor
    - in monitor, 34
    - persistence of, 37
    - SNR differences, 188
  - photometer, 15, 149
  - photometry, 11
  - photomultiplier tube, 238
  - photopic vision, 115
  - physical domain, 53
  - physical measures, 53
  - physically realizable colors, 18
  - picture archiving and communication, 207
  - pincushion, 203
  - pixel
    - aspect ratio, 162, 170
    - decimation, 163
    - defects, 182–183, 193
    - density, 55, 162–163, 171
    - fill factor, 57
    - intensity transforms, 219
    - pitch, 55
    - processing, 219
      - operations, 233
      - transforms, 1
    - replication, 163, 228
    - size, 55
    - subtense, 57
  - plasma display panels, *see* PDP
  - point source, 11
  - polarization, 42, 111
  - polarizers, 41
  - polynomial, 211
  - portrait monitor mode, 30
  - position controls, 47
  - power, as unit of measure, 11
  - power saver, 215
  - presbyopes, 121
  - primary colors, 17
  - primary diagnosis, 199
  - printer
    - calibration, 254
    - look-up table (LUT), 254
    - operation, 249
    - quality, 249
    - selection, 249
    - setup, 254
  - printing procedures, 254
  - prints, 1
  - prismatic diffuser, 207
  - probability of detection, 100
  - probability of false alarms, 101
  - processor, 5
  - progressive scan, 36
  - projection displays, 258
  - protective covering of prints, 254
  - pseudocolor, 49, 133, 223
  - pulmonary nodules, 142
  - pupil diameter, 105
  - purchasing advice, 8
- Q**
- quality, 6, 29, 53
  - quantization, 212
  - quantizing, 32
- R**
- radar imagery, 206, 213
  - radiant energy, 11, 34
  - radiograph, 1, 144
  - radiography, 145
  - radiologists, 142
  - radiometric fidelity, 239–240, 249, 251
  - radiometry, 11
  - random access memory (RAM), 34
  - resolution-addressability ratio (RAR), 59, 175
  - raster
    - modulation, 62
    - pattern, 48
    - stability, 77
  - recalibration, 215
  - receiver operating characteristic, 100
  - reconnaissance and surveillance community, 2
  - reflectance, 68, 147
  - reflected light, 15
  - refresh rate, 33, 48, 74, 181–183, 201
  - relative edge response, 59
  - resolution, 53, 258
    - and cost trade-off, 243
    - conversion, 240
    - reduced, 233
  - resolution-addressability ratio, 59
  - resolvable pixels, 61
  - retina, 105
    - periphery of, 107
  - retinal illuminance, 105
  - RGB model, 24
  - ringing, 75, 182–183
  - roam, 227
  - rods, 107
  - Rogers and Carel, 168, 212
  - room lighting, 2
  - rotation, 227
- S**
- saccades, 102, 109
  - saccadic distances, 110
  - saturation, 17, 23, 223
  - scan rate, 189
  - scanner, selection of, 237
  - scanning, 243

photometer, 173  
process, 102  
spectroradiometers, 26  
scotopic vision, 115  
screen  
  aspect ratio, 162, 170  
  buffer, 34  
  saver, 215  
  size, 54, 162, 170  
search  
  pattern, 102  
  process, 102  
  task, 102  
sensitivity function, 11  
separable acuity, 111  
sequential color separation, 40  
setup of printer, 254  
shadow mask, 40  
shielding, 209  
signal, 99  
  amplitude, 34  
  plus noise, 99  
signal-to-noise ratio, *see* SNR  
silver halide printers, 249  
size/resolution requirements  
  of color monitor, 161  
  of monochrome monitor, 162  
slide scanners, 238  
SMPTE target, 202  
Snellen letter, 87  
SNR, 71, 182, 193  
solid angle, 13  
spatial, 53, 77  
  fidelity, 239, 249  
  filtering, 224  
  filters, 219  
  integration process, 126  
speckle, 130  
spectral, 77  
  color, 53  
  sensitivity, 11  
spectroradiometer, 26  
specular reflections, 68  
spot growth, 140  
spot size enlargement factor, 247  
standard sensitivity function, 12  
steradian, 13  
stereo acuity, 111, 117  
stereoscopic, 110  
Stiles-Crawford effect, 107  
storage  
  and processing device, 5  
  and verification, 243  
straightness, 75, 183, 188, 193  
subjective  
  performance, 82  
  quality ratings, 83

  quality scale, 85  
  ratings, 81  
subtractive color concept, 25  
supertwisted nematic (STN), 42  
swim, 74, 181, 183, 189  
synthetic aperture radar, 130, 224

## T

tasks, 6  
temperature, 11  
temporal, 53, 77  
theory of signal detection (TSD), 2, 99  
thermal printers, 249  
TIFF, 248  
timing conflicts, 203  
tonal color transfer, 251  
tonal transfer adjustment (TTA), 220  
  linear, 221  
  nonlinear, 221  
tonal transfer correction (TTC), 220  
transmittance, 68  
transparency, 255  
tri-bar, 87  
trichromatic theory of vision, 110  
tristimulus values, 18  
troland, 105  
TSD, *see* theory of signal detection  
TTA, *see* tonal transfer adjustment  
TTC, *see* tonal transfer correction  
twisted nematic (TN), 41  
two-dimensional FFT, 226

## U

undershoot, 69  
Uniform Chromaticity Spacing (UCS),  
  20  
uniform perceptual brightness, 256  
unsharp masking, 226  
utility of displayed image, 53, 81

## V

validation, 87  
value of displayed image, 53  
vernier acuity, 111  
vertical grill, 40  
vertically slotted mask, 40  
VGA refresh rate, 33  
video  
  amplifier, 203  
  card, 5  
  controllers, 31  
viewgraphs, 1  
viewing, 110  
  angle, 71

angle threshold, 139, 145, 152  
distance, 57  
visible spectrum, 11  
vision  
  mesopic, 115  
  photopic, 115  
  scotopic, 115  
  trichromatic theory of, 110  
  *see also* HVS, individual eye parts  
visual acuity, 111  
visual angle, 57  
voltage, 34

## W

warm-up time, 74, 148, 181, 188  
warp, 227  
water-soluble ink, 254  
watt, 11

wavefront aberrations, 121  
wavelength, 11, 17  
  band, 11  
  sensitivity, 11  
  spectrum, 11  
wavelet compression, 230  
waviness, 75, 193  
white point, 22

## X

x ray, 1  
xenon, 43  
XGA refresh rate, 33

## Z

Zone A, 162  
Zone B, 162





Jon Leachtenauer received his A.B. and M.S. degrees in Geology from Syracuse University. After serving as a photointerpreter in the U.S. Army, he began a 40-year career in human factors research in image quality and image interpretation performance measurement. He has worked for Aero Service Corporation, Photonics Research Corporation, the Boeing Company, and ERIM. While at ERIM, he was the Senior Scientist for the Imagery Analysis Division of the National Exploitation Laboratory. He formed a consulting company in 1999

(J/M Leachtenauer Associates) and is currently a consultant to the National Imagery and Mapping Agency and the U.S. Army Night Vision and Electronic Sensors Directorate. He also conducts research in image and display quality and medical automation. With Ronald Driggers, he is the author of *Surveillance and Reconnaissance Imaging Systems: Performance Prediction and Modeling*. He is a contributor to the *Encyclopedia of Optical Engineering* and other books, and is responsible for numerous technical reports and published papers. He is a member of SPIE, SID, OSA, Sigma Xi, and IS&T.