PROCEEDINGS OF SPIE

Millimetre Wave and Terahertz Sensors and Technology V

Neil A. Salmon Eddie L. Jacobs Editors

26–27 September 2012 Edinburgh, United Kingdom

Sponsored by SPIE

Cosponsored by SELEX GALILEO • THALES

Delivered with the support of Scottish Development International • Scottish Enterprise

Cooperating Organisations

DSTL (United Kingdom) • IOP Instrument Science and Technology Group (United Kingdom) Scottish Optoelectronics Association (United Kingdom) Electronics Sensors and Photonics Knowledge Transfer Network (United Kingdom)

Published by SPIE

Volume 8544

Proceedings of SPIE 0277-786X, V.8544

SPIE is an international society advancing an interdisciplinary approach to the science and application of light.

Millimetre Wave and Terahertz Sensors and Technology V, edited by Neil A. Salmon, Eddie L. Jacobs, Proc. of SPIE Vol. 8544, 854401 \cdot © 2012 SPIE \cdot CCC code: 0277-786/12/\$18 \cdot doi: 10.1117/12.2011757

The papers included in this volume were part of the technical conference cited on the cover and title page. Papers were selected and subject to review by the editors and conference program committee. Some conference presentations may not be available for publication. The papers published in these proceedings reflect the work and thoughts of the authors and are published herein as submitted. The publisher is not responsible for the validity of the information or for any outcomes resulting from reliance thereon.

Please use the following format to cite material from this book:

Author(s), "Title of Paper," in *Millimetre Wave and Terahertz Sensors and Technology V*, edited by Neil A. Salmon, Eddie L. Jacobs, Proceedings of SPIE Vol. 8544 (SPIE, Bellingham, WA, 2012) Article CID Number.

ISSN: 0277-786X ISBN: 9780819492852

Published by

SPIE

P.O. Box 10, Bellingham, Washington 98227-0010 USA Telephone +1 360 676 3290 (Pacific Time) · Fax +1 360 647 1445 SPIE.org

Copyright © 2012, Society of Photo-Optical Instrumentation Engineers.

Copying of material in this book for internal or personal use, or for the internal or personal use of specific clients, beyond the fair use provisions granted by the U.S. Copyright Law is authorized by SPIE subject to payment of copying fees. The Transactional Reporting Service base fee for this volume is \$18.00 per article (or portion thereof), which should be paid directly to the Copyright Clearance Center (CCC), 222 Rosewood Drive, Danvers, MA 01923. Payment may also be made electronically through CCC Online at copyright.com. Other copying for republication, resale, advertising or promotion, or any form of systematic or multiple reproduction of any material in this book is prohibited except with permission in writing from the publisher. The CCC fee code is 0277-786X/12/\$18.00.

Printed in the United States of America.

Publication of record for individual papers is online in the SPIE Digital Library.



Paper Numbering: Proceedings of SPIE follow an e-First publication model, with papers published first online and then in print and on CD-ROM. Papers are published as they are submitted and meet publication criteria. A unique, consistent, permanent citation identifier (CID) number is assigned to each article at the time of the first publication. Utilization of CIDs allows articles to be fully citable as soon as they are published online, and connects the same identifier to all online, print, and electronic versions of the publication. SPIE uses a six-digit CID article numbering system in which:

- The first four digits correspond to the SPIE volume number.
- The last two digits indicate publication order within the volume using a Base 36 numbering system employing both numerals and letters. These two-number sets start with 00, 01, 02, 03, 04, 05, 06, 07, 08, 09, 0A, 0B ... 0Z, followed by 10-1Z, 20-2Z, etc.

The CID Number appears on each page of the manuscript. The complete citation is used on the first page, and an abbreviated version on subsequent pages. Numbers in the index correspond to the last two digits of the six-digit CID Number.

Contents

Conference Committee

vii	Introduction
SESSION 1	SYSTEMS I
8544 02	Development of passive submillimeter-wave video imaging systems for security applications (Invited Paper) [8544-1]
	E. Heinz, T. May, D. Born, G. Zieger, A. Brömel, S. Anders, V. Zakosarenko, T. Krause, A. Krüger, M. Schulz, F. Bauer, HG. Meyer, Institut für Photonische Technologien e.V. (Germany)
8544 03	SUMIRAD: a near real-time MMW radiometer imaging system for threat detection in an urban environment [8544-2]
	S. Dill, M. Peichl, D. Rudolf, Deutsches Zentrum für Luft- und Raumfahrt e.V. (Germany)
8544 04	IMAGINE project: a low cost, high performance, monolithic passive mm-wave imager front-end [8544-3]
	N. Alexander, GATE S.A. (Spain); P. Frijlink, OMMIC (France); J. Hendricks, Rogers BVBA
	(Belgium); E. Limiti, TECS S.R.L. (Italy); S. Löffler, RHe Microsystems GmbH (Germany); C. Macdonald, Rogers BVBA (Belgium); H. Maher, OMMIC (France); L. Pettersson, D. Platt,
	Acreo AB (Sweden); P. Rice, GATE S.A. (Spain); M. Riester, D. Schulze, Dyconex AG (Switzerland); V. Vassilev, Chalmers Univ. of Technology (Sweden)
8544 05	Interferometric aperture synthesis for next generation passive millimetre wave imagers
	[8544-4] N. A. Salmon, P. Wilkinson, C. Taylor, The Univ. of Manchester (United Kingdom)
SESSION 2	SYSTEMS II
054407	2D millionalisa sugara accompanies lumanos and navada (Invited Dance) [05.44.5]
8544 06	3D millimetre-wave scanner for luggage and parcels (Invited Paper) [8544-5] H. Essen, R. Zimmermann, Maxonic GmbH (Germany); S. Hantscher, Fraunhofer FHR (Germany); N. Pohl, Ruhr-Univ. Bochum (Germany)
8544 08	Characterisation and calibration of a large aperture (1.6 m) ka-band indoor passive millimetre wave security screening imager [8544-7]
	N. A. Salmon, L. Kirkham, P. N. Wilkinson, The Univ. of Manchester (United Kingdom)
SESSION 3	DEVICES
8544 OC	Components, concepts, and technologies for useful video rate THz imaging [8544-11] A. Bergeron, M. Terroux, L. Marchese, O. Pancrati, M. Bolduc, H. Jerominek, INO (Canada)

8544 0D	Amorphous semiconducting Y-Ba-Cu-O: a silicon-compatible material for IR uncooled sensitive detection with microsecond response time [8544-12] A. J. Kreisler, V. S. Jagtap, A. F. Degardin, SUPELEC/LGEP, CNRS (France) and UPMC, Univ. Paris 6 (France) and Univ. Paris Diderot (France)
8544 OE	Amplitude and intensity interferometry using satellite LNB receivers for innovative and low cost microwave and millimetre wave sensor development [8544-13] N. A. Salmon, J. Radiven, P. N. Wilkinson, The Univ. of Manchester (United Kingdom)
8544 OF	Innovative monolithic detector for tri-spectral (THz, IR, Vis) imaging [8544-14] S. Pocas, CEA-LETI-Minatec (France); M. Perenzoni, N. Massari, Fondazione Bruno Kessler (Italy); F. Simoens, J. Meilhan, W. Rabaud, S. Martin, B. Delplanque, P. Imperinetti, V. Goudon, C. Vialle, A. Arnaud, CEA-LETI-Minatec (France)
8544 0G	Micro-machined millimeter wave sensor array for FM radar application [8544-15] J. Trontelj, A. Sešek, Univ. of Ljubljana (Slovenia)
SESSION 4	IMAGE PROCESSING AND PHENOMENOLOGY
8544 OH	Simulating the operation of millimeter-wave imaging systems (Invited Paper) [8544-17] R. Appleby, S. Ferguson, Queen's Univ. Belfast (United Kingdom)
8544 01	A millimetre-wave MIMO radar system for threat detection in urban environments [8544-18] A. J. Kirschner, J. Guetlein, S. Bertl, J. Detlefsen, Technische Univ. München (Germany)
8544 OJ	Real-time computer processing of image from THz passive imaging device for improving of images [8544-20] V. A. Trofimov, V. V. Trofimov, Lomonosov Moscow State Univ. (Russian Federation)
	POSTER SESSION
8544 OK	Perimeter surveillance using a miniaturized millimetre-wave radar [8544-21] H. Essen, Maxonic GmbH (Germany); W. Johannes, S. Stanko, Fraunhofer-FHR (Germany)
8544 OM	Hot electron bolometer for detection of fast terahertz pulses from optical parametric oscillator [8544-23] N. Palka, P. Zagrajek, Military Univ. of Technology (Poland); A. Czerwinski, Warsaw Univ. of Technology (Poland); T. Trzcinski, E. Rurka, M. Szustakowski, Military Univ. of Technology (Poland); M. Sypek, Warsaw Univ. of Technology (Poland)
8544 ON	Improvement of passive THz camera images [8544-24] M. Kowalski, M. Piszczek, N. Palka, M. Szustakowski, Military Univ. of Technology (Poland)
	Author Index

Conference Committee

Symposium Chairs

David H. Titterton, Defence Science and Technology Laboratory (United Kingdom)

Reinhard R. Ebert, Fraunhofer-Institut für Optronik, Systemtechnik und Bildauswertung (Germany)

Conference Chairs

Neil A. Salmon, MMW Sensors Ltd. (United Kingdom) **Eddie L. Jacobs**, The University of Memphis (United States)

Conference Programme Committee

Amir Abramovich, Ariel University Center of Samaria (Israel)
Nicholas J. Bowring, Manchester Metropolitan University
(United Kinadom)

Markus Peichl, Deutsches Zentrum für Luft- und Raumfahrt e.V. (Germany)

Douglas T. Petkie, Wright State University (United States) **Christopher A. Schuetz**, Phase Sensitive Innovations, Inc. (United States)

Session Chairs

Systems I

Neil A. Salmon, MMW Sensors Ltd. (United Kingdom)Nicholas J. Bowring, Manchester Metropolitan University (United Kingdom)

Eddie L. Jacobs, The University of Memphis (United States)

2 Systems II

Stephan Dill, Deutsches Zentrum für Luft- und Raumfahrt e.V. (Germany)

Eddie L. Jacobs, The University of Memphis (United States)

3 Devices

Douglas T. Petkie, Wright State University (United States) **Neil A. Salmon**, MMW Sensors Ltd. (United Kingdom)

4 Image Processing and Phenomenology Amir Abramovich, Ariel University Center of Samaria (Israel) Eddie L. Jacobs, The University of Memphis (United States)

Proc. of SPIE Vol. 8544 854401-6

Introduction

A diversity of millimetre wave and terahertz sensors and technology continues to be developed. Contributors strive to understand and satisfy end user requirements whilst offering performance improvements to the systems, subsystems and devices at lower costs, so as to meet market expectations. The understanding of signatures and the means to simulate signatures and images in passive and active systems improves each year, and this year is no exception. Below is a brief description of the topics covered in this year's conference.

Systems

An impressive 350 GHz stand-off detection system, using 64 element superconducting transition edge sensors (TES) was demonstrated. Using a closed cycle cooler and a helium evaporation the detectors in the system operate at below 1 Kelvin. It demonstrates a compact format and high performance imagery, with a video rate NETD at well below 1 K and a spatial resolution in imagery of 2 cm at a range of 10 m.

Collaborative efforts continue between the defence end user communities and research groups to investigate sensor fusion in the recognition of IEDs. The system of this consortium combines w-band passive millimetre wave imaging and a MIMO E-band 72-79 GHz radar. The system is mounted on a vehicle and up-dates a one frame per second, combining data from IR and visible sensors to provide good receiver operational characteristics in the detection of threats.

Efforts to reduce costs and improve performance of 'walk-by' airport security screening imaging systems have been made. The consortium develops improved package and system performance of the w-band imager by designing receiver module that integrates feeds, MMIC based LNAs, and zero-biased detectors.

Innovation in sensor development is investigated by exploiting lower cost sensors using satellite LNBs at 10-12 GHz. The packaged devices offer RF and IF amplifiers, local oscillators and filters at a cost three orders of magnitude less than receivers at w-band. The system could be used as the basis for a next generation aperture synthesis imager.

The radio astronomy technology of aperture synthesis is investigated for near-field security screening. The development and use of simulation tools to examine the performance of next generation three dimensional aperture synthesis security screening portals is presented. These systems will generate images with tens of thousands of pixels.

Development of synthetic aperture radar (SAR) systems for luggage inspection at w-band is demonstrated, showing range resolution of 7 mm. The system uses low noise, medium power HEMT amplifiers and multipliers based on SiGe technology and SAR processing using back-projection algorithms. The system has a radiation bandwidth >25 GHz and a phase locked loop for stabilisation operating at a signal bandwidth of 100 MHz.

A perspective from the radio astronomy community is provided by presenting a system for measuring the cosmic background (CMB). The system is a polarimetric sensor operating at 90 GHz and 150 GHz using 1000 transition edge (TES) bolometers and 500 feedhorn-coupled polarimeters. It uses a SQUID readout operating at a temperature of 100mK with the critical temperature of the detector being 150 mK.

The characterisation of large 1.6 m aperture ka-band indoor passive millimetre wave security screening imager is presented. This identifies the phenomenon of self-emission as a limiting factor in high RF gain based passive imagers used in security screening portals. The work also quantifies millimetre wave emission from fluorescent lights which if used in the neighbourhood of a security screening system can also limit system performance. For longer periods (30s) of integration, a 200 mK sensitivity was demonstrated. Replacement amplifiers will provide a greatly improved performance, enabling this system to demonstrate portal screening phenomenology and capability at ka-band.

Perimeter surveillance at 94 GHz using change detection and 360° azimuthal scanning is presented. The system operates to a range of 500 m and radar returns are compared with templates for recognition.

Devices

Biased and unbiased millimetre wave video detectors over the band 100 GHz to 400 GHz are developed, using planar GaAs (forward biased) and InGaAs (zero biased) air-bridged Schottky diodes. These devices are integrated with planar antennas and microstrip readout circuits. Radiation is focused on the planar antennas using high resistivity Si hemispherical lenses.

Efforts continue to develop yttrium-barium-copper cuprate (YBCO) (frequently used in the infrared region as a microbolometer) for the detection of millimetre and terahertz radiation. Work continues in the area of monolithic 200 mm CMOS Si wafer development which integrates bolometer focal plane arrays (having 160x160 elements) with readout electronics, in an attempt to integrate THz, IR, and visible sensors into a single focal plane array.

Silicon wafer micromachining to build titanium based 16 element microbolometer arrays coupled to micro-antennas at 300 GHz to 800 GHz is explored. The signal

bandwidth is 150 kHz and the NEP is 10 pW/root Hz. Target applications are associated with FM radars.

Hot electron bolometers are used to detect radiation generated by a parametric oscillator at 0.7 to 2.5 THz.

Theoretical studies of broadband THz emission from laser induced charge acceleration in semiconductor materials continues.

Phenomenology

Improvements in the understanding of signatures are presented in these papers, where scattering of clothing at 100 GHz and 300 GHz is quantified. The principal component analysis technique is used to analyse the spectra of energetic materials as a means to aid recognition.

Scene simulation for passive millimetre wave imaging using the open-source software is demonstrated. This offers an attractive route to having a simulation capability to investigate the performance of systems in new scenarios.

Our thanks to everyone who helped make this year's meeting such a success. We look forward to another engaging conference next year in Dresden.

Neil A. Salmon Eddie L. Jacobs

Proc. of SPIE Vol. 8544 854401-10